

13.

FB 638999185 A



EBC-SP-db 641394

501

BATTERIES WITH TESTER LABELCasper
2/23/91Background of the Invention

This invention relates to batteries that have a tester included in the label on the battery.

Some typical battery testers are multilayer strips. There is generally a substrate layer onto which is deposited an electrically conductive layer that has terminal end portions. Also disposed on the substrate is a thermally sensitive material. This material changes color when heated and is in thermally transferable contact with the electrically conductive layer. When the terminals of the tester strip are placed in contact with the corresponding terminals of a battery heat will be generated in the conductive layer. The amount of heat generated is proportional to the remaining power of the battery. The heat is then transferred to the thermally sensitive material causing it to change color. These tester strips are available individually and in association with a package containing the batteries.

One disadvantage with the currently available tester strips is that the strip or package can become separated

from the batteries to be tested. Because of their shape and style, the testing strips can be easily misplaced or discarded as trash. Thus, when a need arises to test batteries, it may be difficult to locate the tester strips.

5 Also, the individual tester strips are difficult to use.

In view of these disadvantages, a tester in close association with the batteries to be tested is desired.

Summary of the Invention

This invention is a battery to which is attached a
10 label that contains a tester for the battery. The label is comprised of a tester circuit that has a first end to make contact with a first terminal of the battery and a second end to make contact with a second terminal of the battery. These ends are electrically connected to each other via an
15 area of controlled resistivity. The tester circuit is insulated from the battery terminals except for the first and second terminal contact ends. An indicating material is disposed over and in responsive contact with the area of controlled resistivity of the tester circuit.

20 In another aspect, this invention is a battery to which is attached a label that contains a tester for the battery. The label is comprised of:

a) a tester circuit comprised of an electrically conductive material, and that has a first terminal contact end and a second terminal contact end connected to each other via an area of controlled resistivity;

b) an indicating material disposed in responsive contact with the area of controlled resistivity of the tester circuit; and

c) a first terminal connector that connects the first terminal contact end of the tester circuit with a first terminal of the battery, and a second terminal connector that connects the second terminal contact end of the tester circuit with a second terminal of the battery, which terminal has a polarity opposite that of the first terminal;

wherein at least one of the terminal contact ends of the tester circuit is positioned out of contact with its respective terminal connector to provide an open tester circuit.

In yet another aspect, this invention is a battery to which is attached a label that comprises means for testing the capacity of the battery and a means for indicating the capacity of the battery. The testing means comprises means
5 for completing a circuit between the terminals of the battery. The means for indicating the capacity of the battery is in responsive contact with the means for testing the capacity of the battery.

In still yet another aspect this invention is a process
10 for attaching a label comprised of a tester for a battery to a battery, comprising the steps of:

- a) applying a conductive layer to a nonconductive base film layer, wherein the conductive layer has first and second terminal contact ends that
15 are electrically connected to each other via an area of controlled resistivity;
- b) placing an indicating material in responsive contact with the area of controlled resistivity; and
- 20 c) adhering the surface of the nonconductive base film layer opposite the surface on which the

conductive layer is deposited to the housing of the battery.

The batteries of this invention have testers built into the label so that whenever it is desired, the battery can be tested. The batteries are easily tested by completing the tester circuit in the label and without the use of components not associated with the battery or label.

Brief Description of the Drawings

Figure 1A shows an exploded view of a multilayered label that has a single switch area, and Figures 1B and 1C show the switch area.

Figure 2 shows an exploded view of a multilayered label that has two switch areas.

Figure 3 shows an alternative embodiment of the dual switch multilayered label.

Figure 4 shows an alternative embodiment of the dual switch multilayered label.

Figure 5 shows an alternative embodiment of the dual switch multilayered label.

Figure 6B shows a battery to which is attached a tester label, and Figure 6A shows a front view of an assembled label.

Figure 7A shows the area of contact between the tester circuit and a terminal of the battery, and 7B is an enlargement of that area.

Figure 8 shows a two-ply label containing a tester circuit for a battery.

Figure 9 shows a stepwise method for making a label with a tester circuit for a battery.

Figure 10 shows an alternative stepwise method for making a label with a tester circuit for a battery.

Detailed Description of the Invention

The batteries useful in this invention are primary or secondary batteries that have positive and negative terminals. The batteries are generally comprised of an anode, a cathode and electrolyte contained in a sealed housing. The housing typically has an opening in one end that is sealed and closed with a cover. This cover is usually in electrical contact with either the cathode or anode to provide a terminal of the battery.

The label is comprised of a means for testing the capacity of the battery. This means is comprised of a means for completing the circuit between the terminals of the battery, a means for responding to the capacity of the battery and a means for indicating the capacity of the battery. The means for completing the circuit can be a tester circuit that is comprised of an electrically conductive material. The electrically conductive material can be a metallic foil, or a metallized plastic layer. Other examples include electrically conductive paints or inks, such as those that contain graphite, carbon or metals or combinations thereof as the conductive materials. The electrically conductive material is configured to have first and second ends that are connected to each other via an area of controlled resistivity. The first end is provided to make contact with a first terminal of the battery, and the second end is provided to make contact with a second terminal of the battery. These terminal contact ends are or will be connected to the terminals of the battery to complete the tester circuit. Thus, when the tester circuit is completed, electric current can flow through the area of controlled resistivity. By "controlled resistivity" is meant that the resistance is controlled to be within the range to activate the responsive means.

The resistance in the area of controlled resistivity can vary or it can be constant. In one embodiment it is desired to have a varying resistance to indicate relative remaining useful life of a battery. For example, the
5 current flowing through the tester circuit will generate a specific temperature. The temperature achieved will be proportional to the amount of current supplied by the battery. Thus, the area of controlled resistivity can be tapered or of varying thicknesses to achieve a temperature
10 gradient. Alternatively, the area can be of constant width and constant thickness. A further alternative could involve the use of different conductive materials having different resistivities in the area of controlled resistivity. In addition, when using thermochromic materials, materials
15 activated at different temperatures could be used along an area of constant resistance, or continuous or discontinuous segments of a thermochromic material could be used along an area of variable resistance.

The testing means can be further comprised of
20 means for connecting the tester circuit to the terminals of the battery. This means can be terminal connectors that connect the battery terminals with the terminal contact ends of the tester circuit. The terminal contact ends of the tester circuit can be in direct contact with the terminals
25 of the battery. However, this is only desirable when the

circuit will place a very low drain on the battery so that the battery is not prematurely discharged.

Preferably, either one or both terminal contact ends of the circuit are out of contact with the terminals of the battery so that the tester circuit is open. In this embodiment, the testing means is further comprised of means for switching the tester circuit on. The tester circuit could have one or more switches. In a preferred embodiment of the invention either the anode or cathode is in electrical contact with the conductive housing of the battery. In this embodiment, one of the terminal contact ends of the tester circuit can be connected to the housing, or positioned out of contact with the housing, for example by a small opening in a layer disposed between the housing and the end of the tester circuit. This opening can act as a switch for the tester circuit. By forcing the terminal contact end into contact with the housing through the opening, the switch is closed and the tester circuit is completed to test the battery. This contact can be conveniently made by applying finger or thumb pressure to the switch areas.

It is also desirable that the label comprise one or two terminal connectors that are in contact with the battery terminals. When the tester circuit is used, the terminal

contact ends of the tester circuit will be in contact with these terminal connectors. These terminal connectors can be in the form of conductive tabs. In one embodiment, a conductive cover acts as one terminal for the battery and
5 one of the conductive tabs is in electrical contact with this cover.

The testing means further comprises a means for indicating the capacity of the battery. The indicating means will be in responsive contact with the area of
10 controlled resistivity and will respond to and indicate a state that is present in that area. For example, a temperature will be generated in that area when a current flows through the tester circuit. Also, the current itself can indicate such a state. If the indicating means will be
15 a thermally sensitive material, then it is in thermally transferable contact with the area of controlled resistivity. If the indicating means will be an electrical field or voltage sensitive material, then the indicating means will be in electrical contact with the area of
20 controlled resistivity. The indicating means will indicate to the consumer the capacity of the battery. This indication can be qualitative such as a "good" or "bad" reading, or quantitative such as a remaining percentage of useful life.

In one embodiment, the indicating means can be a thermally sensitive material that is in thermally transferable contact with the area of controlled resistivity of the tester circuit. Thus, the heat generated in the area of controlled resistivity in the tester circuit can be transferred to the thermally sensitive material. The thermally sensitive materials change color in response to a temperature change. The material is readily viewable to a consumer and so the consumer, based on the color change, can determine whether the battery is good or needs to be replaced. Examples of such thermally sensitive materials are liquid crystal materials and thermochromic inks. The indicating material can be used singly or in combination. For example, in one embodiment different layers of the indicating material are employed. The layers are activated at different temperatures or states and can be designed to change different colors at different temperatures. For example, the layer of material activated at the highest temperature will preferably be the bottom layer, and the upper layers are arranged in decreasing temperature of activation with the lowest temperature material in the top layer.

Examples of suitable liquid crystal materials are of the cholesteric type, such as cholesteryl oleate, cholesteryl chloride, cholesteryl caprylate and the like.

Examples of suitable thermochromic inks include those comprised of a dye, developer and desensitizing agent that are disclosed in U.S. Patent 4,835,475, herein incorporated by reference. Inks can be obtained from Japan Capsule
5 Products and Sakura Color Products Corp.

In another embodiment, the indicating and responding means can be materials that respond to a voltage change or electric field. These materials are responsive directly to the remaining capacity of the battery as the current flows
10 through the tester circuit, and so will be disposed in electrically responsive contact with the area of controlled resistivity. Materials for this purpose are known as electrochromic materials and are commercially available from the Donnelly Corporation, for example.

15 The labels useful in this invention can also comprise additional insulative layers, printing layers, protective layers and the like. Suitable materials for use as the different layers are those typically used in battery labels and include plasticized or unplasticized polyvinyl chloride
20 (UPVC), metallic films, paper and the like, and they are prepared by known methods, such as laminating the layers together. The label can be attached to the battery by the use of an adhesive. The label can be in the form of

individual sheets which will have a seam or in the form of a shrinkable tube in which a battery is encased.

A preferred tester label is comprised of a base insulative layer adhered to the housing of the battery. The housing is in electrical contact with either the anode or cathode of the battery. The insulative layer has an opening in it. The tester circuit is placed on the surface of this insulator. One of the terminal contact ends of the circuit is aligned with the opening in the insulator. The other terminal contact end of the circuit is in contact with the terminal of the battery that is not in contact with the housing. The indicating material is placed over the area of controlled resistivity of the circuit. The indicating material can be placed directly on the tester circuit or it can be placed on a separate layer that is placed over the tester circuit. Preferably, the indicating material is a thermochromic ink and is in thermally transferable contact with the area of controlled resistivity. Finally, a protective layer is placed over the indicating material. The type of protective layer is selected so that the indicating material can be observed by the user. To test the battery, the user will press the label at the point above the opening in the insulator layer to establish contact between the terminal contact end of the circuit and the conductive battery housing. As the circuit is

completed, a temperature will be generated in the area of controlled resistivity which will be transferred to the indicating material. If the desired temperature is reached, the indicating material will so indicate and the user can
5 determine the amount of capacity remaining in the battery.

To prepare the individual sheet labels, a shrinkable plastic film can be printed with a thermally sensitive material in a test window area. Any graphics to be included can also be printed on this film. On the reverse side of
10 this film the electrically conductive tester circuit is printed, and an insulative layer is placed over this conductive layer. The insulative layer prevents the conductive layer from contacting the battery housing and provides thermal and electrical insulation. The insulative
15 layer can completely cover the conductive layer, and terminal connectors can be used to connect the battery terminals with the terminal contact ends of the tester circuit. Alternatively, openings can be left in the insulative layer through which the conductive portion of the
20 tester circuit can be directly connected to the terminals of the battery. An adhesive is added to the back of the label, except for the portion in which the tester circuit will contact the terminals. The tester circuit can also be printed on a continuous layer of adhesive. The adhesive
25 side of the label is then joined to a releasable material

such as a silicone paper web to form a label carrier. The labels can then be die cut and converted to rolls ready for use.

To prepare the labels on a shrinkable tube, after
5 forming the label as generally described above the label is placed around a mandrel and welded lengthwise to form a tube. The tube is then wound on a roll and is ready for use.

In forming the labels, it is desirable that the
10 insulative layers be built up around any openings between the battery terminals and the ends of the tester circuit. This increased thickness will assist in preventing accidental activation of the tester and resultant premature discharge of the battery.

15 In a preferred method, unplasticized polyvinyl chloride (UPVC) film can be metallized, e.g., aluminized, on one surface. The UPVC film will provide an insulative layer and the metallized layer can provide the conductive layer of the label. Portions of the conductive layer can be removed to
20 establish positive and negative terminal contact ends of the tester circuit and an area of controlled resistivity. The portions can be removed by chemical etching or by photo resist techniques. Alternatively, the deposition of the

metallic layer can be done in the desired tester circuit pattern. Another layer of insulation, such as an additional PVC or a UV-cured coating, such as those employing epoxy resin, is deposited over the conductive layer. Areas of the
5 conductive layer are exposed through this insulative layer to provide switch contact areas. One or more switch areas can be provided. Advantageously, a relatively thick layer of additional insulative material can be placed around the switch areas to increase the distance needed to close the
10 switch and thus to ensure against inadvertent closure. A foaming ink is suitable for this purpose. This insulative layer can also be placed over the area of controlled resistivity. An adhesive layer can then be placed over this insulative layer. The adhesive layer will have openings in
15 it so that the conductive layer can contact the terminals of the battery. This partial label can then be laminated to a carrier web, such as silicone-coated paper.

On the other surface of the UPVC layer is deposited an indicating material. The preferred indicating material for
20 this embodiment is thermally sensitive, such as a thermochromic ink. This material is placed over the area of controlled resistivity of the tester circuit. This outer layer can also contain printing and graphics. The final layer is a protective coating or film deposited over the
25 indicating material.

The layers and steps described above can be altered or reversed in many ways to provide the label with a tester circuit.

Referring to the Figures, Figure 1A shows an exploded
5 view of a tester label 1. Insulative layer 5 has opening 7.
On one side of insulative layer 5 is adhesive layer 3. This
side of the label 5 will be adhered to the conductive
housing of a battery. On the surface of insulative layer 5
opposite the surface containing adhesive layer 3, is a
10 tester circuit 10. The tester circuit 10 can be located
directly on the surface of insulative layer 5. The tester
circuit 10 is comprised of an electrically conductive
material and has a first terminal contact end 12 disposed
over opening 7 in the insulator layer 5. Connected to the
15 first terminal contact end 12 is an area of controlled
resistivity 14. This area is connected to the second
terminal contact end in the form of tab 15 that can be
placed in contact with a terminal of the battery. Over the
tester circuit 10 is disposed label substrate 17. This
20 layer comprises thermally sensitive material 19. This layer
can also contain printing and can be made of plastic. This
layer further comprises switch area 20 that is aligned with
the first terminal contact end 12 and opening 7. Thus, the
tester circuit 10 can be completed by establishing contact

between first terminal contact end 12 through opening 7 to a conductive battery housing by depressing switch area 20.

The thermally sensitive material 19 is disposed in thermally transferable contact with the area of increasing resistivity 14 of tester circuit 10. Optionally, protective layer 18 can be placed over label substrate layer 17. Each of the individual layers can range in thickness from about 0.5 to about 2 mils (i.e. from about 0.0005 to about 0.002 inch, or from about 12 to about 50 microns).

10 Figure 1B shows a side view of a portion of an assembled label attached to a battery. Label 1 has insulative layer 5 adhered to can 2 by adhesive layer 3. Insulative layer 5 has opening 7. Next to the insulative layer 5 is end 12 of the tester circuit 10. The label 1 is
15 completed with label substrate layer 17 next to tester circuit 10 and has protective layer 18 disposed on top of it.

In Figure 1C, the tester label 1 is activated by depressing the label at the switch area 20 over opening 7.
20 Thus, end 12 of tester circuit 10 is placed in contact with can 2.

In Figure 2, label 1 has the same adhesive layer 3, the same label substrate layer 17, and optional protective layer

18 as the label in Figure 1. Insulative layer 6 in Figure
2 has an opening 8 and a tab 19. An additional insulative
layer 21 is disposed on one surface of the first insulative
layer 6. This additional insulative layer 21 has an opening
5 24 aligned with opening 8 in the first insulative layer 6,
and a second opening 25 aligned with a portion of the tab
19. Over the second insulative layer 21 is disposed tester
circuit 28. This tester circuit has a first terminal
contact end 29 aligned with opening 24 in the second
10 insulative layer 21 and a second terminal contact end 30
aligned with the second opening 25 in the second insulative
layer 21. The tester circuit 28 has an area of controlled
resistivity 32 connecting first terminal contact end 29 and
second terminal contact end 30. Label substrate layer 17
15 contains thermally sensitive material 22 in alignment with
the tester circuit area 32. The label substrate layer 17
has two switch areas 33 and 34. Switch area 33 is aligned
with the first terminal contact end 29 of the tester circuit
28, and switch area 34 is aligned with the second terminal
20 contact end 30 of tester circuit 28.

In Figure 3, label 1 has the same protective layer 18,
adhesive layer 3 and label substrate layer 17 as shown in
the other figures. Additionally, the label 1 has an
insulative layer 36 having a positive terminal connector 38
25 and a negative terminal connector 39. Positive terminal

connector 38 has a tab 40 that will contact the positive terminal of the battery, and negative terminal connector 39 has a tab 41 that will contact the negative terminal of the battery. Next to insulative layer 36 is disposed a second
5 insulative layer 37. This insulative layer 37 has a first opening 42 aligned with the positive terminal connector 38, and a second opening 43 aligned with the negative terminal connector 39. The next layer 44 in label 1 contains the tester circuit 45 that has first terminal contact end 47
10 and second terminal contact end 48 connected to each other via an area of controlled resistivity 50. The first terminal contact end 47 is aligned with the first opening 42 in insulative layer 37, and the second terminal contact end 48 is aligned with the second opening 43. Label substrate
15 17 which is disposed over tester circuit layer 44 has a first switch area 51 and a second switch area 52, and has thermally sensitive material 49. The first switch area 51 is aligned with first terminal contact end 47 of tester circuit 45, and the second switch area 52 is aligned with
20 second terminal contact end 48. Because insulative layer 37 has openings 42 and 43, tester circuit 45 is open. Both contact ends 47 and 48 are out of contact with the battery terminals. By pressing both switch areas 51 and 52, terminal contact ends 47 and 48 can be placed in contact
25 with terminal connectors 38 and 39 through openings 42 and 43 to complete the tester circuit 45.

The label 1 depicted in Figure 4 has the same layers as the label in Figure 3. Area of controlled resistivity 50 and thermally sensitive material 56 in Figure 4 are configured to run axially along the side of the battery to
5 be labelled.

The label 1 depicted in Figure 5 has the same layers and tester circuit configuration as the label 1 in Figure 4. The label 1 in Figure 5 has an insulative layer 57 that contains an opening 58 and a negative terminal connector 39.
10 Opening 58 permits contact between end 47 of tester circuit 55 and the housing of a battery to be labelled.

Figure 6A shows a front view of a fully assembled label 1. On label 1, the thermally sensitive material 60 is visible and will run axially along the side of the battery.
15 Switch areas 62 and 63 are also visible. Tab 65 of tester circuit 61 can be seen to extend beyond the length of label 1.

In Figure 6B, label 1 of Figure 6A has been adhered to a battery 64. Terminal contact tab 65 is shown as extending
20 over and in contact with the bottom 66 of battery 64. In this tab configuration, it can be desirable to have a recessed area in the battery can bottom for the tab to rest.

Switch areas 62 and 63 are shown to be on diametrically opposite sides of the battery 64 and can be readily activated by thumb and forefinger pressure.

In Figures 7A and 7B, the bottom of a battery and the
5 tab contact between the tester circuit in the label and a
battery terminal are shown. In 7A, the battery has
container 70 with opening 72. The opening 72 is closed with
first cover 73 that contacts anode current collector 75.
Cover 73 is sealed and secured to container 70 by seal 71.
10 Insulative annular washer 74 is placed over the opening 72
in container 70. Negative cover 76 is disposed over the
annular washer 74 and is in contact with the anode current
collector 75 to provide the negative terminal for the
battery. Label substrate end 86 of label 80 extends over
15 onto negative cover 76.

In 7B, the encircled portion of Figure 7A is enlarged.
The label 80 has insulative layer 81 disposed next to
container 70. The terminal contact tab 82 is an extension
of the tester circuit of the label and extends over and
20 into contact with cover 76 at area 83. The label substrate
end 86 extends completely over terminal contact tab 82 to
conceal it. To complete labelling of the battery, the
extension of label substrate 86 is heat-shrunk over and

around the periphery of cover 76 to insure good electrical contact between contact tab 82 and cover 76.

In Figure 8 a two-ply label is shown. Label 90 has base insulative film 91 with opening 92 and tester circuit 5 93. Tester circuit 93 has terminal contact tab 94 , area of controlled resistivity 95 and terminal contact end 96. Protective layer 97 is placed over base film layer 91. As the label 90 is applied onto a battery, opening 92 will be aligned with terminal contact end 96.

10 In Figure 9, the steps for making the label with a tester are shown. In Steps 1 to 6, the label is viewed from the backside and in Steps 7 to 9 the label is viewed from the front side. In step 1, a base film layer 101 of PVC is aluminized. In Step 2, a portion 102 of the aluminum is
15 removed in the pattern of the tester circuit 103. Next, an electrical insulator is applied in Step 3 onto the aluminized surface 105 with ends 106 and 107 exposed to provide contact with the terminals of the battery. Extra insulation 108 is applied in Step 4 to area 104 of the
20 tester circuit 103 and ends 106 and 107. In Step 5, a pressure sensitive adhesive 109 is applied to the surface of the label, and in Step 6 the label is applied to a silicone coated paper 110. In Step 7, the opposite side of the base PVC film 101 is printed with the label graphics 111. In

Step 8, the thermochromic ink 112 is placed over the area 104 of the tester circuit 103, and a protective film 113 is applied over the label. Finally, in Step 9, the label is die cut at points 114 to provide the individual labels.

5 The steps can be reversed as shown in Figure 10 with the outer protective layer forming the initial layer. The label is viewed from the back or the battery side. In Step 1, the protective film 121 is formed. In Step 2, the thermochromic ink 122 is placed on the film. The label is
10 printed with graphics 123 in Step 3, and is laminated to aluminized PVC in Step 4. The aluminized surface 124 is on the surface of the PVC opposite of the surface next to the protective film 121. In Step 5 the aluminized layer is etched in the tester circuit pattern 125 with area of
15 controlled resistivity 126. In Step 6 an electrical insulator is applied over the aluminized surface 124 of the PVC film. Ends 127 and 128 are exposed to provide terminal contact ends for the tester circuit. In Step 7 additional insulation is placed around area 126 and ends 127 and 128 of
20 the tester circuit. Adhesive is applied over the insulator in Step 8 and the label strip is laminated to a silicone coated paper support 129 in Step 9. Finally, In Step 10 the labels are die cut at 130 to the proper size.

The tester circuit shown in these Figures can of course be varied. Also the portion of the metallized surface can be exposed at different areas to provide different switch areas. To provide shrink tube labels, the labels can be
5 formed according to the above steps and then applied around a mandrel and welded to form a tube.